

Date: Jul.19,2022 Page 1 of 6 Report No: TST20220760132-6EN

Applicant/ Dongguan Mitte Sports Goods Co., LTD Manufacturer:

No.21 xiling Road, Dongkeng Town, Dongguan city, Guangdong Province, China Address:

The following sample(s) was /were submitted and identified on behalf of the clients as:

Sample Name : Bicycle helmet

Model No. BK-4 **Labeled Age Grading** : 12Y+ **Requested Age** : 12Y+

Age Group Assessed As

Per Age

: 12Y+

Sample Received Date : Jul.12,2022

: Jul.12,2022To Jul.19,2022 **Testing Period**

: EN 1078:2012+A1:2012 **Test Requested**

Test Method : Please refer to next page(s). **Test Result**

: Please refer to next page(s).

Signed for and on behalf of

Andy Zheng Technical Director



Report No: TST20220760132-6EN Date: Jul.19,2022 Page 2 of 6

Test Conducted: Based on EN 1078:2012+A1:2012

Helmets for pedal cyclists and for users of skateboards and roller skates

Test Results: Details shown as following table

Clause	Test Method/Requirement	Result
4.1	Materials For those parts of the helmet coming into contact with the skin, the material used should be known not to undergo appreciable alteration from contact with sweat or with substances likely to be found in toiletries. Materials shall not be used which are known to cause skin disorders.	PASS
4.2	Construction The helmet normally consists of a means of absorbing impact energy and means of retaining the helmet on the head in an accident. The helmet should be durable and withstand handling. The helmet shall be so designed and shaped that parts of it (visor, rivets, ventilators, edges, fastening device and the like) are not likely to injure the user in normal use. NOTE: Helmets should: have low weight; be ventilating; be easy to put on and take off; be usable with spectacles; not significantly interfere with the ability of the user to hear traffic noise.	Pass See annex 1
4.3	Field of vision When tested in accordance with 5.7 there shall be no occultation in the field of vision bounded by angles as follows (see Figure 1): - horizontally: min. 105°from the longitudinal vertical median plane to the left and right hand sides; - upwards: min. 25°from the reference plane; - downwards: min. 45°from the basic plane.	Pass See annex 4
4.4	Shock absorbing capacity The helmet shall give protection to the forehead, rear, sides, temples and crown of the head. When tested in accordance with 5.3 and 5.4 the peak acceleration shall not, for each impact, exceed 250 g for the velocity of 5,42 +0.1,-0 m/s on the flat anvil, and 4,57+0.1,-0 m/s on the kerbstone anvil. NOTE: These are theoretically equivalent to 1 497 mm and 1 064 mm drop heights respectively.	Pass See annex 2
4.5	Durability After being tested the helmet shall not exhibit damage that could cause significant injury to the wearer (sharp edges, points).	Pass
4.6	Retention system	



Report No: TST20220760132-6EN Date: Jul.19,2022 Page 3 of 6

Clause	Test Method/Requirement	Result				
	General					
4.6.1	Means shall be provided for retaining the helmet on the wearer's head. All parts of the retention system shall be securely attached to the helmet.					
	Chin strap					
4.6.2	The chin strap shall not include a chin cup. Any chin strap shall be no less than 15 mm wide. Chin straps may be fitted with means of enhancing comfort for the wearer.					
	Fastening device					
4.6.3	Any retention system shall be fitted with a device to adjust and maintain tension in the system. The device shall be capable of adjustment so that the buckle does not sit on the jaw bone.	Pass				
	Color					
4.6.4	No part of the retention system shall be colored green.	Pass				
	NOTE: It is recommended that the opening mechanism be marked with red or orange color.					
	Strength					
	When tested in accordance with 5.5, the dynamic extension of the retention system shall not exceed					
	35 mm and the residual extension shall not exceed 25 mm. For this purpose, extension includes slippage of the fastening device.					
4.6.5						
4.0.3	Damage to the retention system shall be accepted provided that the above requirements are met.					
	NOTE : In this test, slippage of the fastening device can be measured and recorded separately from other contributions to the					
	extension but this is for information only and is not subject to a separate requirement.					
4.6.6	Effectiveness	Pass				
	When tested in accordance with 5.6 the helmet shall not come off the headform.					
	Ease of release					
4.6.7	Following the strength test in accordance with 5.5 and with the load still applied, it shall be	Pass				
	possible to open the release system with one hand.					
	Inspection and determination of mass					
	Inspect the helmet to ascertain whether it is suitable for its intended purpose and fulfils the general					
5.2	requirements in 4.2.					
	Determine the mass of the helmets of the same size submitted for testing. Calculate and record					
	the mean value in g rounded off to the nearest 10 g, stating the size of the helmet.					
	Marking First believe the library deal in a section in the library in the librar					
	Each helmet shall be marked in such a way that the following information is easily legible by the user and is likely to remain legible throughout the life of the helmet:					
6		Pass				
	a. the number of this European standard; b. the name or trademark of the manufacturer;	Pass				
	c. the designation of the model;	Pass				
	c. the designation of the model,	1 ass				



Report No: TST20220760132-6EN Date: Jul.19,2022 Page 4 of 6

Clause	Test Method/Requirement		
	d. the designation, which shall be one or more of the following:-helmet for pedal cyclists, skateboarders or roller skaters;	Pass	
	e. the size or size range of the helmet, quoted as the circumference (in centimeters) of the head which the helmet is intended to fit;		
	f. the weight of the helmet (the average mass in g determined according to EN 1078,5.2);	Pass	
	g. year and quarter of manufacture;	Pass	
6	h. a label carrying the instructions – "Warning! This helmet should not be used by children while climbing or doing other activities when there is a risk of strangulation/hanging if the child gets trapped with the helmet"		
	In addition, if the helmet has components made of material which are known to be adversely affected by contact with hydrocarbons, cleaning fluids, paints, transfers or other extraneous additions, the helmet shall carry an appropriate warning.	Pass	
	If there is a consumer sales packaging, the information specified in a), b), d), and h) shall also be given on that package. The text shall be of minimum font size 12.	Pass	
	Information supplied by the manufacture		
	With every helmet clear information in the language of the country of sale shall be given as follows:	Pass	
	a. that the helmet can only protect if it fits well and that the buyer should try different sizes and choose the size which feels secure and comfortable on the head;	Pass	
7	b. that the helmet should be adjusted to fit the user, e.g. the straps positioned so that they do not cover the ears, the buckle positioned away from the jawbone and the straps and buckle adjusted to be both comfortable and firm;	Pass	
7	c. how the helmet should be positioned on the head to ensure the intended protection is provide (e.g. that it should be placed so as to protect the forehead and not be pushed too for over the back of the head); to protect the forehead and not be pushed too for over the back of the head);		
	d. that a helmet cannot always protect against injury;	Pass	
	e. that a helmet subjected to a severe impact should be discarded and destroyed;	Pass	
	f. a statement of the danger of modifying or removing any of the original component parts of the helmet other than as recommended by the manufacturer, and that helmets should not be adapted for the purpose of fitting accessories in a way not recommended by the manufacturer.	Pass	



Report No: TST20220760132-6EN Date: Jul.19,2022 Page 5 of 6

Annex-1: Mass

Mass of the samples:

Sample No.	Mass (g)		
1	210		

Annex-2: Impact energy attenuation test

Test Specification: BS EN 1078:2012+A1:2012-5.4 Ambient temperature at time of test: 23.2 °C

Condition		Test Anvil	Test site	Velocity (m/s)	Peak'G	Result
	High temperature No recondition (Clause 5.4.2.1)	Kerbstone	Front	5.41	125.2	Pass
,		Flat	Left	5.35	118.6	Pass
	Low temperature No recondition (Clause 5.4.2.2)	Flat	Crown	5.33	115.7	Pass
		Kerbstone	Left rear	5.41	121.4	Pass
	Artificial Ageing No recondition (Clause 5.4.2.3)	Kerbstone	Left front	5.33	117.6	Pass
		Flat	Rear	5.32	121.4	Pass

Annex-3: Retention system strength

Test Specification: BS EN 1078:2012+A1:2012-5.5 Ambient temperature at time of test: 23.2 °C

Condition	Dynamic extension (mm)	Residual extension (mm)	Result
Low temperature No recondition (Clause 5.4.2.2)	26.1	12.1	Pass
Artificial Ageing No recondition (Clause 5.4.2.3)	27.6	12.9	Pass

Annex-4: Field of vision

Test Specification: BS EN 1078:2012+A1:2012-5.7

Horizontal: >105° Upward: >25° Downward: >45°



Report No: TST20220760132-6EN Date: Jul.19,2022 Page 6 of 6

Sample photo:



*** End of Report ***